

**DECLARATION OF PERFORMANCE****No: BDX**


1. Unique identification code of the product type: **BDX**
2. Intended use/es: Thermal insulation in buildings
3. Manufacturer: **VELUX A/S, Ådalsvej 99, DK-2970 Hørsholm, [www.velux.com](http://www.velux.com)**
5. Systems of assessment and verification of constancy of performance (AVCP): System
6. Harmonised standard: EN 16069:2012+A1:2015, Notified body/ies: 0761, 1004
7. Declared performance:

Essential characteristics	Performance	§	NB*
Reaction to fire	E	4.2.6	0761
Release of dangerous substances to the indoor environment	npd	4.3.13	
Acoustic absorption index	npd	4.3.11	
Direct airborne sound insulation index	npd	4.3.9	
Continuous glowing combustion	npd	4.3.15	
Thermal resistance	$\lambda_D$ : 0.039 W/(m·K)	4.2.1+4.2.3	1004
Water permeability	npd	4.3.7.1+4.3.7.2	
Water vapour permeability	npd	4.3.8	
Compressive strength	npd	4.3.3-3.3.6	
Durability of reaction to fire against heat, weathering, ageing/degradation	npd	4.2.7	
Durability of thermal resistance against heat, weathering, ageing/degradation	npd	4.2.1+4.2.7	
Durability of compressive strength against ageing/degradation	npd	4.3.6	
NPD: No performance determined			
* Notified body/ies: <a href="http://ec.europa.eu/growth/tools-databases/nando/">http://ec.europa.eu/growth/tools-databases/nando/</a>			

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Klaus Lorentzen, Vice President  
 Ådalsvej 99, DK 2970 – Hørsholm, 8 July 2022

		<b>BDX</b> Thermal insulation in buildings		Harmonised standard: <b>EN 16069:2012+A1:2015</b>	
Essential characteristics	Performance	S	NB #		
Reaction to fire	E	4.2.6	0761		
Release of dangerous substances to the indoor environment	npd	4.3.13			
Acoustic absorption index	npd	4.3.11			
Direct airborne sound insulation index	npd	4.3.9			
Continuous glowing combustion	npd	4.3.15			
Thermal resistance	$\lambda_D$ : 0.039 W/(m·K)	4.2.1+4.2.3	1004		
Water permeability	npd	4.3.7.1+4.3.7.2			
Water vapour permeability	npd	4.3.8			
Compressive strength	npd	4.3.3-3.3.6			
Durability of reaction to fire against heat, weathering, ageing/degradation	npd	4.2.7			
Durability of thermal resistance against heat, weathering, ageing/degradation	npd	4.2.1+4.2.7			
Durability of compressive strength against ageing/degradation	npd	4.3.6			