

DECLARATION OF PERFORMANCE

No: BFX

1. Unique identification code of the product type: BFX
2. Intended use/es: Flexible sheets for underlays for roofs
3. Manufacturer: VELUX A/S, Ådalsvej 99, DK-2970 Hørsholm, www.velux.com
5. Systems of assessment and verification of constancy of performance (AVCP): System 3
6. Harmonised standard: EN 13859-1:2014. Notified body/ies: 0338
7. Declared performance:

Essential characteristics	Performance	§	NB #
Reaction to fire:	class E	4.3.1	0338
Resistance to water penetration: - before artificial ageing - after artificial ageing	class W1 class W1	4.3.2	0338
Tensile strength in longitudinal direction: - before artificial ageing - after artificial ageing	200 N/50 mm 120 N/50 mm	4.3.4	0338
Tensile strength in transverse direction: - before artificial ageing - after artificial ageing	200 N/50 mm 120 N/50 mm	4.3.4	0338
Elongation in longitudinal direction: - before artificial ageing - after artificial ageing	NPD NPD	4.3.4	-
Elongation in transverse direction: - before artificial ageing - after artificial ageing	NPD NPD	4.3.4	-
Resistance to tearing: - Longitudinal direction - Transverse direction	NPD NPD	4.3.5	-
Flexibility at low temperature (pliability)	NPD	4.3.7	-
Artificial ageing behaviour, concerning - Resistance to water penetration - Tensile strength	NPD NPD	4.3.8	-

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Klaus Lorentzen, Vice President
Ådalsvej 99, DK 2970 – Hørsholm 8 July 2022

UK CA 22	BGX Flexible sheets for underlays for roofs	Harmonised technical specification: EN 13859-1:2014	
Essential characteristics	Performance	§	NB #
Reaction to fire:	class E	4.3.1	0338
Resistance to water penetration: - before artificial ageing - after artificial ageing	class W1 class W1	4.3.2	0338
Tensile strength in longitudinal direction: - before artificial ageing - after artificial ageing	200 N/50 mm 120 N/50 mm	4.3.4	0338
Tensile strength in transverse direction: - before artificial ageing - after artificial ageing	200 N/50 mm 120 N/50 mm	4.3.4	0338
Elongation in longitudinal direction: - before artificial ageing - after artificial ageing	NPD NPD	4.3.4	-
Elongation in transverse direction: - before artificial ageing - after artificial ageing	NPD NPD	4.3.4	-
Resistance to tearing: - Longitudinal direction - Transverse direction	NPD NPD	4.3.5	-
Flexibility at low temperature (pliability)	NPD	4.3.7	-
Artificial ageing behaviour, concerning - Resistance to water penetration - Tensile strength	NPD NPD	4.3.8	-