



- ① VELUX flashing (EBW-BK 35°-70°)
- ② VELUX window (GGL 15°-90°)
- ③ VELUX underfelt collar (BFX)
- ④ VELUX insulation frame (BDX)
- ⑤ VELUX vapour barrier (BBX)
- ⑥ VELUX vapour barrier tape (BBX)
- ⑦ Gasket on BBX in window rebate
- ⑧ VELUX Support rafter
- ⑨ Craftman lining
- ⑩ Installation batten (Non VELUX)
- ⑪ Trimmer where necessary (Non VELUX)
- ⑫ Felt/breather membrane (Non VELUX)

Roof covering:
Tiles
 Max 120 mm

VELUX Products:
GGL
 15°-90°

EBW--BK
 35°-70°

BFX

BDX

BBX

A°	min. B mm
35°	2003
40°	2171
45°	2328
50°	2470
55°	2600
60°	2714
65°	2815
70°	2900

VELUX window sizes:

Size	Width (mm)
MK--	780
PK--	942
SK--	1140

Size	Height (mm)
-K06	1178

Roof opening Section A-A:

Size	Roof opening (mm)
MK06 --22BK	1679
PK06 --22BK	2003
SK06 --22BK	2399
MK06 --32BK	2477

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks



File name: EBW--BK-GGL-VAS-223-0616			
Drawing no.:---		SCo: ---	
Create date: 10.06.2016	Rev. date:	Format: A3	Scale: 1:5

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.