



- VELUX Products:
- BFX
 - BDX
 - GGL 15°-90°
 - LS-BBX
 - VFE 90°
 - LVI-BBX
 - EFL 15°-55°
 - SLATES < 8 mm

Sheer plan perpendicular to roof

| 15°-55° | A mm | B mm |
|---------|------|------|
| 15 | 50 | 40 |
| 20 | 55 | 45 |
| 25 | 60 | 45 |
| 30 | 65 | 50 |
| 35 | 70 | 55 |
| 40 | 75 | 60 |
| 45 | 85 | 65 |
| 50 | 95 | 75 |
| 55 | 105 | 85 |

VFE/VFA/VFB

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks

VELUX VELUX A/S

| | | | |
|--|--|--------------------------------------|------------------------------|
| VELUX Roof Window GGL + VFE installed in slates VELUX insulation collar BDX and under felt collar BFX VELUX flashing EFL VELUX lining LS- + LVI and vapour barrier collar BBX | Date 29.10.10 All measurement in mm | File name EFL-VAS-203-1010 | Drawing no. - - |
|--|--|--------------------------------------|------------------------------|

SCo

Note:
 When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.

