



- ① VELUX flashing (EAW-21E 10°-75°)
- ② VELUX window (GGL 15°-90°)
- ③ VELUX underfelt collar (BFX)
- ④ VELUX vapour barrier (BBX)
- ⑤ VELUX vapour barrier tape (BBX)
- ⑥ Gasket on BBX in window rebate
- ⑦ VELUX Support Rafter
- ⑧ Craftman lining (Non VELUX)
- ⑨ Installation batten (Non VELUX)
- ⑩ Trimmer (Non VELUX)
- ⑪ Felt/breather membrane (Non VELUX)

Roof covering:

**Tiles**  
Max 120 mm

VELUX Products:

**GGL**  
15°-90°

**EAW-21E**  
10°-75°

**Support Rafter**

**BFX**

**BBX**

VELUX window sizes:

Size	Width (mm)
FK--	660
MK--	780
PK--	942
SK--	1140
UK--	1340

Roof opening for VELUX Support Rafter:

Size	Height (mm)	Size	L2 (mm)
-K04	978	-K04	1720
-K06	1178	-K06	1990
-K08	1398	-K08	2290
-K10	1600	-K10	2565

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks



File name: EAW-21E-GGL-VAS-146-0616			
Drawing no.:---		SCo: ---	
Create date: 30.05.2016	Rev. date:	Format: A3	Scale: 1:5

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.