




VELUX FS Fixed Skylight installation guidelines for roofs with roof pitch less than 15 degrees


For roofs with roof pitches less than 15 degrees, the VELUX FS Fixed Skylight must be installed to a min. 15 degrees. A purpose made flashing designed to meet the conditions set out in Section E2 of the New Zealand Building Code shall be manufactured and installed by a specialist flashing contractor. This flashing must be guaranteed against weather-tightness by the specialist flashing contractor. Insulation material meeting the requirements of NZBC/H1 is required in the cavities of the lightwell structure.



ELEVATION



SECTION A-A



SECTION B-B

SUGGESTED INSTALLATION - FS FIXED SKYLIGHT IN MEMBRANE ROOFS (PITCH < 15 DEGREES)

This drawing is an instrument of service and is provided for informational use only.

© 2011 VELUX GROUP

| | | | | | |
|--|--|-------------------------|--|-------------|---------|
| VELUX | | NEW ZEALAND LTD. | | Name | Date |
| Sky-Product Management | | 0800 650 445 | | Drawn by | June 11 |
| | | | | Checked by | June 11 |
| | | | | Drawing No. | |
| FS - Fixed Skylight in Membrane Roof (pitch <15 degrees) | | | | | |

© VELUX is a registered trademark