



- ① ODN flashing (20°-90°)
- ② VELUX window (GGL 20°-90°)
- ③ VELUX underfelt collar (BFX)
- ④ VELUX insulation frame (BDX)
- ⑤ VELUX vapour barrier (BBX)
- ⑥ VELUX vapour barrier tape (BBX)
- ⑦ Gasket on BBX in window rebate
- ⑧ VELUX Lining (LS-)
- ⑨ Installation batten (Non VELUX)
- ⑩ Trimmer where necessary (Non VELUX)
- ⑪ Felt/breather membrane (Non VELUX)
- ⑫ Navitect II i.p.v. Emergo front adapter (Non VELUX)
- ⑬ Navitect II i.p.v. Emergo side adapter (Non VELUX)  
- Gray RAL 7043 Gloss 30  
- Black RAL 9005 Gloss 30

Roof covering:



VELUX Products:



VELUX window sizes:

| Size | Width (mm) | Size | Height (mm) |
|------|------------|------|-------------|
| MK-- | 780        | -K08 | 1398        |
| PK-- | 942        |      |             |

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks

|                                    |            |               |               |
|------------------------------------|------------|---------------|---------------|
| <b>VELUX</b>                       |            |               |               |
| File name: EMERGO-GGL-VAS-805-1118 |            |               |               |
| Drawing no.:---                    |            | SCo: ---      |               |
| Create date:<br>26.11.2018         | Rev. date: | Format:<br>A3 | Scale:<br>1:5 |

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.