

Product information

VELUX Sun tunnels for pitched tiled roofs TWF/TWR

TWF



TWR



Product description

- VELUX sun tunnels are complete installation kits with all necessary components for both exterior and interior connections
- Exterior rooflight module with
 - 4 mm toughened glass pane with easy-to-clean coating
 - integrated polyurethane flashing
 - removable sash
- Two tunnel types
 - TWF - with flexible tunnel
 - TWR - with rigid tunnel
- Interior light diffuser unit
 - frosted, two-layer light diffuser with EdgeGlow (removable inner pane for easy cleaning)
 - integrated ceiling trim ring
- For information on VELUX sun tunnels
 - TLF/TLR for pitched roofs and flat roofing materials
 - TCF for flat roofs
 see separate Product information sheets

Roof pitch

- Can be installed in roof pitches between 15° and 60°

Materials

- Toughened glass, exterior glass pane
- Polyurethane, frame with integral flashing
- Plastic, sash
- Fibreglass yarn or aluminium with reflective coating, tunnels
- Polyethylene (PE) foil, vapour barrier collar
- Polycarbonate, interior light diffuser
- Plastic, integrated ceiling ring

Downloads

For installation instructions and CAD drawings, please visit www.velux.co.uk

Certifications




The VELUX product factories guarantee quality systems implementation process and environmental management systems through appropriate accreditations ISO 9001 and ISO 14001

EUTR In compliance with the EU Timber Regulation (EUTR), EU regulation 995/2010

REACH We are aware of the REACH regulation and acknowledge the obligations. No products are obliged to be registered in accordance to REACH and none of our products contain any Substances of Very High Concern.

Available sizes



VELUX sun tunnels are available in two sizes:

- TWF is available in size OK14
- TWR is available in sizes OK10 and OK14

Measurements are the tunnel diameters

About VELUX sun tunnels

VELUX sun tunnels **direct the natural light** captured from the sky, through the loft space and into rooms and corridors where installation of traditional VELUX roof windows is either not possible or not appropriate.

VELUX sun tunnels can **transform even the darkest places** that would normally have to do with artificial lighting **into bright and welcoming living areas.**

The reflective tunnel, flexible or rigid, leads the natural daylight from the rooflight module into the building. The design of the tunnel ensures an **exceptional reflection of the incoming daylight.**



The **flexible** tunnel is ideal for distances between roof and ceiling from 0.4 to 1.5 m.


- flexible fibreglass
- high reflective coating
- tunnel diameter 350 mm




The **rigid** tunnel is ideal for distances between roof and ceiling from 0.9 to 1.7 m - with extension sections up to 6 m.

- extension sections 600/1200 mm
- rigid aluminium
- super high reflective coating
- tunnel diameter 250/350 mm
- Easy to assemble with Flexi Loc™

Horizontal section



Vertical section



Variants and sizes

	TWF	TWR
Sizes	OK14	OK10 OK14
Roof pitch	15°-60°	
Roofing material	Profiled roofing materials	
Exterior rooflight module	<ul style="list-style-type: none"> • Polyurethane frame with integral flashing, black <ul style="list-style-type: none"> • removable sash • 4 mm toughened glass • easy-to-clean coating (outside) 	
Tube	<ul style="list-style-type: none"> • Flexible tube • fibreglass • high reflective coating 	<ul style="list-style-type: none"> • Rigid tube • 2 straight sections plus 2 adjustable elbows • aluminium • super reflective coating • 98% internal reflection rate
Standard tunnel length	2.0 m	1.7 m
Length including tunnel extension sections ZTR	-	Up to 6.0 m
Interior light diffuser unit	<ul style="list-style-type: none"> • frosted, two-layer polycarbonate light diffuser <ul style="list-style-type: none"> • integrated ceiling ring, white 	

Visible features

TWF



1 Rooflight module

The square rooflight module is installed flush with the roofing material. The design matches VELUX roof windows. An easy-to-clean coating on the outside keeps the glass cleaner for longer.



2 Integrated flashing

The black, polyurethane flashing is integrated with the rooflight module, which makes installation fast and simple.



5 Vapour barrier collar


Vapour barrier collar BBX is supplied with the sun tunnel to ensure a tight connection between the sun tunnel and the existing vapour barrier of the house.



6 Flexible tunnel

A high reflective coating along the interior of the flexible tunnel provides an excellent reflection rate.

TWR



3 Ceiling ring

Seen from the inside, the sun tunnel ends in a frosted light diffuser discretely framed by a white ceiling ring.



4 Light diffuser with EdgeGlow

The discreet light diffuser is designed with EdgeGlow, a new ring of clear glass around the edge of the light diffuser that spreads the light better in the room and offers unique light effects.




7 Super reflective coating

A super reflective coating along the interior of the rigid tunnel provides a 98% internal reflection rate - ensuring that almost all natural light reaching the exterior pane is transferred to the room below.



8 Rigid tunnel - with Flexi Loc™

The rigid tunnel and tunnel extension sections ZTR feature Flexi Loc™ clip system for easy and fast tunnel assembly.



9 Rigid tunnel - elbow

Rigid elbow section - adjustable 0°-45°



10 Rigid tunnel - straight section

Accessories



Extension section ZTR for rigid tunnel

Extension section ZTR is used to extend rigid sun tunnel TWR when the distance from roof to interior ceiling level exceeds 1.70 m. The rigid tunnel can be extended with sections of ZTR up to a maximum of 6.0 m.

- Extension section ZTR
- features Flexi Loc™ clip system for easy and fast tunnel assembly
 - is available in lengths of 600 mm/1200 mm



Ventilation outlet ZTV

Ventilation outlet ZTV is a supplement to an existing ventilation fan in the room.

- Ventilation outlet ZTV
- can be installed in sun tunnels TWF/TWR in size 0K14 only



Light kit ZTL

Light kit ZTL turns the sun tunnel into a lamp when it is dark outside. Low energy LED technology provides dependable light for many years and slim line design minimises shadows on the diffuser pane.


- Light kit ZTL
- can easily be fitted in both new and already installed sun tunnels
 - is supplied with a 4W LED light bulb (corresponds to a 40W incandescent bulb)
 - fits both rigid and flexible sun tunnels in sizes 0K10/0K14



Low U-value kit ZTB

Low U-value kit ZTB 0K14 2002 lowers the U-value in a standard installation. When fitted, there is no visible difference between a sun tunnel with or without the low U-value kit. The same, discrete interior design is maintained.

- Low U-value kit ZTB
- is very easily fitted - together with or after installation of the sun tunnel
 - consists of two layers of acrylic glass and a gasket
 - is available in size 0K14 only



Underfelt collar BFX

Underfelt collar BFX is a pleated collar made of diffusion open material that together with the supplied drainage gutter ensures a tight connection to the underfelt.

Note

We reserve the right to make technical changes.
 For more information on sun tunnels TWF and TWR and other VELUX products, please visit www.velux.co.uk