



DECLARATION OF PERFORMANCE No: BBX / BCX

1. Unique identification code of the product type: **BBX / BCX**
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Flexible sheet for waterproofing
3. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):
VELUX A/S, Ådalsvej 99, DK-2970 Hørsholm, www.velux.com
4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
Not applicable
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
6. In case of a Declaration of Performance concerning a construction product covered by a harmonised standard **EN 13984:2013**:
 - i. **SP Technical Research Institute of Sweden** performed type testing of the following essential characteristic: **Watertightness, Water vapour permeability** under system 3 and issued test report
 - ii. **DBI Danish Institute of Fire and Security Technology** performed type testing of the following essential characteristic: **Reaction to fire** under system 3 and issued test report



7. Declared performance:

Essential characteristics	Performance	§	NB #
Watertightness	passed	5.5	-
Impact resistance	NPD	5.6	-
Durability:		5.7.1+5.7.2	-
- Water vapour resistance after artificial ageing	NPD		
- Chemical resistance	NPD		
Tear resistance	NPD	5.8	-
Joint strength	NPD	5.9	-
Water vapour permeability	Sd = 80 m	5.10	0402
Tensile properties	NPD	5.11	-
Reaction to fire	Class E	5.12	0845


8. Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Not applicable**

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read "Klaus Lorentzen".

Klaus Lorentzen, Vice President, Product Development
Ådalsvej 99, DK 2970 – Hørsholm, 01.08.2017



 Flexible sheet for waterproofing: BBX / BCX		Harmonised technical specification: EN 13984:2013	
Essential characteristics	Performance	§	NB #
Watertightness	passed	5.5	-
Impact resistance	NPD	5.6	-
Durability:		5.7.1+5.7.2	-
- Water vapour resistance after artificial ageing	NPD		
- Chemical resistance	NPD		
Tear resistance	NPD	5.8	-
Joint strength	NPD	5.9	-
Water vapour permeability	Sd = 80 m	5.10	0402
Tensile properties	NPD	5.11	-
Reaction to fire	Class E	5.12	0845